

## CHEMREX® CX-941

Version 1.5

06/27/2006

### 1. PRODUCT AND COMPANY INFORMATION

Company	:	<b>BASF Building Systems</b> 889 Valley Park Drive Shakopee, MN 55379
Telephone	:	952-496-6000
Emergency telephone number	:	(800) 424-9300 (703) 527-3887 (Outside Continental US)
Product name	:	CHEMREX® CX-941
MSDS ID No.	:	10718
TSCA Inventory	:	All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canadian DSL	:	All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).
Product Use Description	:	Adhesive

### 2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
HYDROTREATED MIDDLE PETROLEUM DISTILLATES	64742-46-7		N.E.	N.E.	N.E.	5.00 - 10.00 %
POLYMETHYLENE POLYPHENYL ISOCYANATE	9016-87-9	N.E.	N.E.	N.E.	N.E.	0.00 - 5.00 %
METHYLENE BISPHENYL DIISOCYANATE	101-68-8	0.005 ppm	N.E.	N.E.	0.02 ppm	0.00 - 5.00 %

### 3. HAZARDS IDENTIFICATION

HMIS® Rating	HEALTH 2	FLAMMABILITY 1	PHYSICAL HAZARD 0
WHMIS Class	:	D2B	
Primary Routes of Entry	:	Inhalation Skin contact Eye contact	

#### Effects of Overexposure

Inhalation : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations can cause CNS-depression and narcosis. Prolonged inhalation can be harmful.

## CHEMREX® CX-941

Version 1.5

06/27/2006

- Skin** : Can cause slight irritation. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.
- Eyes** : Can cause slight to moderate irritation, redness, tearing and blurred vision.
- Ingestion** : Intake can cause gastrointestinal irritation and nausea.
- Chronic exposure** : This product contains Crystalline (quartz) Silica which has been listed as a human carcinogen by NTP (Group 1) and IARC (Human Carcinogen) and a Suspected Human Carcinogen by ACGIH (category A2). Repeated or prolonged over exposure to free respirable Crystalline (quartz) silica can cause silicosis or other delayed and serious lung injury. No exposure to respirable Crystalline (quartz) Silica anticipated with recommended use of product. Existing respiratory or skin ailments may be aggravated by exposure. This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal. This product contains isocyanates. Prolonged repeated exposure to isocyanates can lead to skin sensitization. For persons so sensitized even brief exposures to an isocyanate can produce reddening, swelling, rash, or blisters. Similarly, prolonged and repeated exposure to isocyanates can lead to respiratory sensitization. In such individuals, brief exposures to isocyanates at levels well below established exposure limits can produce chemical asthma and nonspecific asthmatic conditions.

### Carcinogenicity

	ACGIH	IARC	NTP	OSHA
HYDROTREATED MIDDLE PETROLEUM DISTILLATES	N.E.	N.E.	N.E.	N.E.
POLYMETHYLENE POLYPHENYL ISOCYANATE	N.E.	No data.	N.E.	N.E.
METHYLENE BISPHENYL DIISOCYANATE	N.E.	No data.	N.E.	N.E.

## 4. FIRST AID MEASURES

- Eye contact** : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact** : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion** : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

## 5. FIRE-FIGHTING MEASURES

- Flash point** : 250.00 °F (121.11 °C) Method: Taglibue C. C.

## CHEMREX® CX-941

Version 1.5

06/27/2006

Autoignition temperature	:	no data available
Lower explosion limit	:	1.6 %(V)
Upper explosion limit	:	10.2 %(V)
Suitable extinguishing media	:	carbon dioxide (CO2) dry chemical water fog
Fire and Explosion Hazards	:	Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.
Special Fire-fighting Procedures	:	As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

Methods for cleaning up	:	Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.
-------------------------	---	--

---

## 7. HANDLING AND STORAGE

---

Handling	:	Keep out of reach of children. For personal protection see section 8.
Storage	:	Keep tightly closed.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Eye protection	:	Wear as appropriate: safety glasses with side-shields goggles face-shield
Hand protection	:	Wear as appropriate: impervious gloves
Body Protection	:	Wear as appropriate: impervious clothing preventive skin protection
Respiratory protection	:	In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
Hygienic Practices	:	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.

## CHEMREX® CX-941

Version 1.5

06/27/2006

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Color : clear

Physical State : liquid

Odor : mild oily

pH : not applicable

Odor Threshold : no data available

Vapor Pressure : no data available

Vapor Density : Heavier than air

Boiling point/range : 342.00 - 514.00 °F (172.22 - 267.78 °C)

Freeze Point : no data available

Water solubility : slightly soluble

Specific Gravity : 1.25

Viscosity : no data available

Evaporation rate : Slower than Butyl acetate

Partition coefficient (n-octanol/water) : no data available

VOC Concentration as applied (less water and exempt solvents) : 45 g/l

---

### 10. STABILITY AND REACTIVITY

---

Stability : Stable under recommended storage conditions.

Conditions to avoid : Prolonged exposure to high temperatures

Materials to avoid : strong oxidizing agents

Hazardous decomposition products : Thermal decomposition:  
MDI vapors

**CHEMREX® CX-941**

Version 1.5

06/27/2006

Irritating or toxic fumes  
Oxides of carbon

Hazardous polymerization : Will not occur under normal conditions.

**11. TOXICOLOGICAL INFORMATION**

**Acute inhalation toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				
HYDROTREATED MIDDLE PETROLEUM DISTILLATES	LC50	no data available		
POLYMETHYLENE POLYPHENYL ISOCYANATE	LC50	no data available		
METHYLENE BISPHENYL DIISOCYANATE	LC50	no data available		

**Acute oral toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Oral)	no data available	
<u>Component</u>			
HYDROTREATED MIDDLE PETROLEUM DISTILLATES	LD50 (Oral)	no data available	
POLYMETHYLENE POLYPHENYL ISOCYANATE	LD50 (Oral)	no data available	
METHYLENE BISPHENYL DIISOCYANATE	LD50 (Oral)	9,200 mg/kg	

**Acute dermal toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Dermal)	no data available	
<u>Component</u>			
HYDROTREATED MIDDLE PETROLEUM DISTILLATES	LD50 (Dermal)	no data available	
POLYMETHYLENE POLYPHENYL ISOCYANATE	LD50 (Dermal)	no data available	
METHYLENE BISPHENYL DIISOCYANATE	LD50 (Dermal)	no data available	

**12. ECOLOGICAL INFORMATION**

Ecotoxicological Information : There is no data available for this product.

**CHEMREX® CX-941**

Version 1.5

06/27/2006

**13. DISPOSAL CONSIDERATIONS**

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

**14. TRANSPORT INFORMATION**

DOT : Proper shipping name Not regulated

IATA : Proper shipping name Not regulated

**15. REGULATORY INFORMATION****SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD

**SARA 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
0.00 - 5.00 %	9016-87-9	POLYMETHYLENE POLYPHENYL ISOCYANATE
0.00 - 5.00 %	101-68-8	METHYLENE BISPHENYL DIISOCYANATE

**CERCLA**

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
5,000 lbs	101-68-8	METHYLENE BISPHENYL DIISOCYANATE

**TSCA Section 12(b) Export Notification**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

**California Proposition 65**

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
14808-60-7	SILICA, CRYSTALLINE QUARTZ

## CHEMREX® CX-941

Version 1.5

06/27/2006

7440-43-9	CADMIUM
7439-92-1	INORGANIC LEAD
7440-38-2	ARSENIC

---

### 16. OTHER INFORMATION

---

Legend : N.E. - Not Established  
TLV - Threshold Limit Value  
STEL - Short Term Exposure Limit  
PEL - Permissible Exposure Limit  
CEIL - Ceiling

Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.